



COOLPIX

At the heart of the image



- 6.0/5.0 megapixels (L11/L10)
- 3x zoom
- 2.4-inch/2.0-inch LCD (L11/L10)
- AA-size battery compatible
- ISO 800 capability



COOLPIX L11 | L10

www.nikon-coolpix.com

Excellence just got easy.

6.0 / 5.0 effective megapixel clarity

Impressively high megapixel counts enable the COOLPIX L11 and L10 to capture images with captivating color and outstanding detail. Such capability also means images can be considerably enlarged, yet still look absolutely stunning.

ISO 800 capability extends shooting in low light

Accurately measuring available light, the L11 and L10 automatically select the best sensitivity setting. And with impressive sensitivity range up to ISO 800, they make it easy to take great-looking pictures in low light conditions.

AA-size battery compatible for power replenishment anywhere

Compatibility with AA-size batteries, which are widely available around the world, means users can go on shooting virtually anywhere without worrying about recharging or running out of power.



Other features

- 2.4-inch LCD (L11)
2.0-inch LCD (L10)
- PictBridge compatible
- Face-priority AF – finds and focuses on people's faces for consistently crisp results
- In-Camera Red-Eye Fix – in-camera compensation for more natural flash portraits
- D-Lighting – adds detail and optimizes exposure to rescue underexposed images

COOLPIX L11 | L10

High ISO
Better pictures in lower light

Simply better portraits

Matte Silver

Matte Black

COOLPIX L11

COOLPIX L10

Nikon COOLPIX L11 / L10 Specifications

Effective pixels:	L11: 6.0 million / L10: 5.0 million
Lens:	3x Zoom-Nikkor; 6.2-18.6mm (35mm [135] format picture angle: 37.5-112.5mm); f/2.8-5.2; 6 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 450mm)
Focus range (from lens):	40cm (1 ft. 4 in.) to infinity (∞), Macro close-up mode: 15cm (5.9 in.) to infinity (∞)
Monitor:	L11: 2.4-in., 115,000-dot, TFT LCD / L10: 2.0-in., 153,000-dot, TFT LCD
Storage media:	Internal memory (approx. 7 MB), SD memory cards
ISO sensitivity:	Auto (auto gain ISO 64-800)
Power source:	Two AA alkaline, oxyride, or lithium batteries, two EN-MH1 rechargeable batteries (optional), EH-65A AC adapter (optional)
Battery life:	Approx. 250 shots with alkaline, 600 shots with lithium, 300 shots with Ni-MH, or 250 shots with oxyride batteries (based on CIPA standard)
Dimensions (WxHxD):	L11: Approx. 89.5 x 60.5 x 27 mm (3.5 x 2.4 x 1.1 in.) excluding projections L10: Approx. 89.5 x 60.5 x 26 mm (3.5 x 2.4 x 1.0 in.) excluding projections
Weight:	L11: Approx. 125 g (4.4 oz.) without battery and SD memory card L10: Approx. 115 g (4.1 oz.) without battery and SD memory card

PictureProject System Requirements

- OS:** **Macintosh:** Mac® OS X version 10.3.9, 10.4.x
Windows: Windows® Vista (32bit), Windows® XP Home Edition/Professional, Windows® 2000 Professional pre-installed models
- Note:** CD-ROM drive required for installation. Only built-in USB ports are supported

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh® and QuickTime® are either registered trademarks or trademarks of Apple Computer Inc. in the United States and/or other countries. The SDHC logo is a trademark. ImageLink and the ImageLink print system logo are trademarks of Eastman Kodak Company. PictBridge is a trademark. D-Lighting technology is provided by Apical Limited. Products and brand names are trademarks or registered trademarks of their respective companies. The FotoNation logo is a trademark. Images on LCDs shown in this brochure are simulated.

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. February 2007 ©2007 NIKON CORPORATION



WARNING TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. SOME DOCUMENTATION IS SUPPLIED ON CD-ROM ONLY.



NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku
Tokyo 100-8331, Japan
<http://nikonimaging.com/>

Nikon Hong Kong Ltd. Suite 1001, 10/F Cityplaza One, 1111 King's Road, Taikoo Shing, Hong Kong www.nikon.com.hk
Nikon Singapore Pte. Ltd. No. 80 Anson Road, Fuji Xerox Towers, #10-01/02, Singapore 079907 www.nikon.com.sg
Nikon (Malaysia) Sdn. Bhd. 11th Floor, Block A, Menara PKNS, No. 17, Jalan Yong Shook Lin, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia www.nikon.com.my
NIKON AUSTRALIA PTY LTD. Unit F1, Lidcombe Business Park, 3-29 Birnie Avenue, Lidcombe NSW 2141, Australia www.nikon.com.au