hp digital projectors sb21 / xb31





HP digital projectors are suited for all professionals. It is outstandingly versatile with an unbeatable mobility - light-weight and easy-to-set-up. HP digital projector is the perfect travelling companion for a mobile professional's presentation needs, either for use in high-powered business presentations or for any discussions and meetings. Catering to a group from 10 to 100 people, there is always one HP digital projector to suit every need and budget.





technical specifications

hp digital projector	xb31	sb21
projection system	Digital Light Processing™ (DLP™)	Digital Light Processing™ (DLP™)
brightness	1500 comparable lumens	1000 comparable lumens
resolution	true XGA (1024 x 768), interpreted SXGA (1280 by 1024) resolution; 16.7 million colours	true SVGA (800 x 600), interpreted XGA (1024 by 768) resolution; 16.7 million colours
contrast	1800:1 JBMA (full on/full off)	1800:1 JBMA (full on/full off)
colour	16.7 million	16.7 million
uniformity	85% (JBMA) optics	85% (JBMA) optics
projection	F/2.44~2.69, f=28.8~34.5 mm 1.2 by manual zoom lens	F/2.4, f=22.4 mm fixed focal lens
throw distance	3.7 to 39.4 feet (1.14 to 12 m)	3.3 to 39.4 feet (1.0 to 12 m)
lens	optical zoom; manual focus	digital zoom; manual focus
video compatibility	NTSC: M (3.58 MHz), 4.43 MHz; PAL: B, D, G, H, I, M, N SECAM: B, D, G, K, K1, L; HDTV: 480i, 480p, 720p, 1080i	NTSC: M (3.58 MHz), 4.43 MHz; PAL: B, D, G, H, I, M, N; SECAM: B, D, G, K, K1, L; HDTV: 480i, 480p, 720p,1080i
computer compatibility	uxga, xga, svga, vga, mac	XGA, SVGA, VGA, MAC
audio	built-in two-watt speaker	n/a
acoustic noise	32 dBA peak under 25° C; 35 dBA typical under 25° C; 39 dBA maximum under 40° C	32 dBA peak under 25° C; 35 dBA typical under 25° C; 39 dBA maximum under 40° C
lamp	150-watt compact P-VIP lamp (user replaceable)	120-watt compact P-VIP lamp (user replaceable)
power supply	Universal AC 100-240V, 50/60 Hz with PFC input	Universal AC 100-240V, 50/60 Hz with PFC input
product certification	FCC Part 15, Class B; CE-Class B; VCC Class B; BSMI; UL; CUL; TÜV-GS	FCC Part 15, Class B; CE-Class B; VCC Class B; BSMI; UL; CUL; TÜV-GS
environmental range	operating: 50 to 104° F (10 to 40° C) storage: - 4 to 140° F (-20 to 60° C)	operating: 50 to 104° F (10 to 40° C) storage: - 4 to 140° F (-20 to 60° C)
dimensions (w x d x h)	8.92 x 7.23 x 2.67 inches (226.5 x 183.6 x 67.75 mm)	7.9 x 5.55 x 2.3 inches (200.7 x 141 x 60.38 mm)
weight (approximate)	3.5 lb (1.6 kg)	2.2 lb (1 kg)
model part numbers	L1511A	L1510A
what's in the box	 hp digital projector xb 31 standard accessories: VESA M1-A-to-D sub and USB cable (1.8 m) 4-pin S-video-to-4-pin S-video cable (1.8 m) RCA jack-to-RCA composite video cable (1.8 m) 2.5 mm phonejack-to-2.5 mm phonejack audio cable wireless remote control with mouse function and laser pointer two batteries tethered lens cap carrying bag multi-language user's guide (CD-ROM) multi-language quick start card support information data sheet 	 hp digital projector sb 21 standard accessories: AC power cord (1.8 m) VESA M1-A-to-D sub and USB cable (1.8 m) USB Mini-B 5-pin-to-4-pin S-video cable (1.8 m) 2.5 mm phonejack-to-RCA composite video cable wireless remote control with mouse function and laser pointer two batteries tethered lens cap carrying bag multi-language user's guide (CD-ROM) multi-language quick start card support information data sheet

Please check with your local Hewlett-Packard sales office or your nearest HP authorised dealer for warranty details.

For more information about hp products and services, please visit our website: **www.hp.com**

authorised dealer

invent



ENERGY STAR is a U.S. registered service mark of the United States Environmental Protection Agency. As an ENERGY STAR partner, HP has determined that this product meets the guidelines for energy efficiency. Apple and Macintosh are trademarks of Apple Computer, Inc. registered in the USA, and other countries. Microsoft, Windows, and Windows NT are registered trademarks of Microsoft Corporation in the USA, and other countries. UNIX is a registered trademark of the Open Group in the USA, and other countries. All other brand and product names are trademarks or registered trademarks of their prescrive companies. The information contained in this document is subject to change without notice. HP makes no warranty of any kind with respect to this information. HP specifically disclaims the implied warranty of merchantability and fitness for a particular purpose. HP shall not be liable for any direct, incidental, consequential, or other damage alleged in connection with the furnishing or use of this information.