

# OLYMPUS®

## CAMERA® C-750 ULTRA ZOOM

Extreme power. Remarkable control. A high-power 10x optical/40x total zoom gets you closer than ever. ED lens elements give you sharp detail and vibrant color. And a 4 megapixel CCD, exposure options, QuickTime movies with sound, a hot shoe and more provide complete creative control. All in a compact, metal-body camera that goes anywhere you do. Nothing's impossible.



[olympusamerica.com/c-750](http://olympusamerica.com/c-750)

**Extraordinary 40x Total Zoom** A new 10x optical zoom lens (38 – 380mm equivalent in 35mm photography) lets you zoom in tighter than ever and zoom back out in an instant. And a 4x digital zoom provides the extended flexibility of a 40x total seamless zoom. Amazing.

**ED Lens Elements** ED glass lens elements ensure sharp detail at all zoom ranges.

**4 Megapixel CCD (Effective)** Perfectly cropped prints 8" x 10" and larger. Small images perfect for e-mail. Every photo is sharp, vibrant and beautiful.

**Exclusive TruePic™ Technology** Uses all pixels at all resolutions, for unmatched detail even at lower resolution settings.

**Total Control** Full auto. Aperture priority. Shutter priority. Manual control. Six Scene Programs. Four customizable My Modes. Take your pick, then take the shot.

**Auto-Connect USB** Connects to nearly any USB computer automatically, including Windows XP and Mac OS X systems.

**QuickTime® Movies with Sound** Instead of sending postcards, shoot a 360° video from the top of a volcano, then e-mail it home to all your envious friends.

**Fantastic Features** Take advantage of countless flash options with the TTL hot shoe. Get extra-large prints from Optimum Image Enlargement mode. An intuitive menu system makes every adjustment easy.



▶ A powerful, versatile Olympus 10x optical zoom lens with ED glass elements lets you capture the details you've never noticed.



CAMEDIA C-750 ULTRA ZOOM Specifications

Stock No. 225390

<b>CCD Imager</b>	4.0 megapixel effective, 4.22 megapixel gross, 1/2.5" (.40") CCD
<b>Lens</b>	Olympus aspherical glass 10x zoom lens 6.3 – 63mm (38 – 380mm equivalent in 35mm photography), 11 lenses in 7 groups
<b>Digital Zoom</b>	Seamless to 40x (10x optical and 4x digital combined)
<b>Aperture Range</b>	f2.8/f3.7 – f8
<b>Shutter Speeds</b>	1/1000 sec. – 16 sec.
<b>ISO</b>	Auto, 100, 200, 400 (equivalent)
<b>Recording Modes</b>	Still image: EXIF 2.2 JPEG, DCF (Design rule for Camera File system), PRINT Image Matching II Movie mode: QuickTime motion JPEG
<b>Optimum Image Enlargement (OIE)</b>	Available 3200 x 2400 image size interpolated from maximum optical CCD resolution of 2288 x 1712
<b>Adjustable Resolutions</b>	3200 x 2400 TIFF, JPEG (SHQ, HQ) Optimum Image Enlargement mode 2288 x 1520 (3:2 format) JPEG (SHQ, HQ) 2288 x 1712 TIFF, JPEG (SHQ, HQ) 2048 x 1536 TIFF, JPEG SQ1 (High, Normal) 1600 x 1200 TIFF, JPEG SQ1 (High, Normal) 1280 x 960 TIFF, JPEG SQ1 (High, Normal) 1024 x 768 TIFF, JPEG SQ2 (High, Normal) 640 x 480 TIFF, JPEG SQ2 (High, Normal)
<b>QuickTime Movie with Sound</b>	33 sec. at 15 fps with sound in 320 x 240 HQ mode 148 sec. at 15 fps with sound in 160 x 120 SQ mode
<b>TruePic</b>	Uses all pixels at all resolutions, Pixel micro-smoothing
<b>Noise Reduction</b>	Available at shutter speeds of 1 sec. or longer
<b>Pixel Mapping</b>	Automatic Pixel Mapping (APM) available via menu setting
<b>DPOF (Digital Print Order Format)</b>	Print reserve (single, all, number of copies), Date or time
<b>Image Shooting Effects</b>	Black and white, Sepia, White board, Black board, 2-in-1 shooting mode
<b>Edit Effects</b>	Still image: Resize, Trimming Movie: Edit, Index
<b>Panorama</b>	Up to 10 frames automatically stitchable with CAMEDIA Master software when using Olympus brand xD-Picture Card™
<b>Sequence</b>	2.6 frames per second burst up to 12 frames in HQ mode
<b>Viewfinder</b>	.44" (1.1 cm) electronic viewfinder (approx. 180,000 pixels)
<b>LCD</b>	1.5" (3.8 cm) low-temperature poly-silicon LCD (approx. 110,000 pixels)
<b>Focusing System</b>	iESP multi-pattern AF (autofocus) TTL system (contrast detection), Spot AF, Selective AF area, Full-Time AF, Manual focusing by gauge

<b>Focusing Ranges</b>	Normal mode: 24" (60 cm) – infinity, Macro mode: 2.8" – 24" (7 cm – 60 cm), Super Macro mode: 1.2" – 2.8" (3 cm – 7 cm)
<b>Exposure Control</b>	Program/Priority modes: f2.8 – f8, 1/1000 sec. – 1/2 sec. Manual: f2.8 – f8, 1/1000 sec. – 16 sec.
<b>Exposure Compensation</b>	± 2 steps EV by 1/3-stop settings, Auto bracketing up to 5 images
<b>Scene Programs</b>	Portrait, Self-portrait, Landscape, Landscape-portrait, Night scene, Sports, 4 My Mode settings (customizable)
<b>Metering System</b>	Digital ESP multi-pattern, Spot, Multi-spot, AE lock, Histogram
<b>White Balance System</b>	iESP multi-pattern auto TTL, One-touch, Pre-set manual (Daylight, Overcast, Tungsten, 3 Fluorescent settings), Manual (-7 red to +7 blue)
<b>Image Adjustments</b>	Sharpness, Contrast, Saturation, Each adjustable +/- 5 steps
<b>Flash</b>	Built-in flash, TTL hot shoe, Modes: Auto for low and backlight, Red-Eye Reduction, Fill-In, Slow Shutter Synchronized (1st curtain and 1st curtain with Red-Eye Reduction), Off
<b>Flash Working Range</b>	Wide: 23" – 16.7' (0.6 m – 5.1 m), Tele: 23" – 12.4' (0.6 m – 3.8 m)
<b>Flash Charging Time</b>	Approx. XX seconds at normal temperature with fully charged battery
<b>Removable Media</b>	3V (3.3V) xD-Picture Card, 16MB card included
<b>Selftimer</b>	12-second delay
<b>Settings Memorization</b>	On/Off (Hold changes/Reset to default settings)
<b>Outer Connectors</b>	USB connector (Auto-Connect), Audio/Video out, DC input
<b>Auto-Connect USB</b>	Compatible with Windows 98 rev2/ME/2000 Pro/XP and Mac OS 8.6 – OS X 10 and higher, Windows 98 rev2 driver provided on CD Mac OS 8.6 requires USB mass storage driver 1.3.5 available at apple.com Downloading to non-USB computer possible with optional card reader
<b>Image Playback</b>	Still image: Single frame, Index display, up to 4x enlargement, Slide show, Scene rotation, Histogram Movie: Normal, Frame-by-frame
<b>Operating Environment</b>	Operation: 32° – 104°F (0° – 40°C) 30 – 90% humidity Storage: -4° – 140°F (-20° – 60°C) 10 – 90% humidity
<b>Power Supply</b>	4 x AA NiMH rechargeable batteries (batteries and charger included) 2 x LB-01 (CR-V3) lithium batteries 4 x AA alkaline batteries 4 x AA lithium batteries C-7AU AC adapter (optional)
<b>Date/Time Calendar</b>	Simultaneous recording into image data, Automatic up to year 2099
<b>Size</b>	4.2" W x 2.6" H x 2.7" D (107.5 x 66 x 68.5 mm) excluding protrusions
<b>Weight</b>	10.4 oz. (295 g) without battery and media card

Available Accessories

Product Number	UPC 050332-	Accessory
200800	295759	B-50SU Quick NiMH Battery and Charger Set
200795	295742	B-60SU Overnight NiMH Battery and Charger Set
200728	123502	B-01 4PE NiMH Battery (4 Battery Cells)
200656	131347	LB-01 2PU CR-V3 Lithium Battery 2-Pack
200685	294707	C-7AU 110V AC Adapter Blister Pack
200862	140578	TCON-17 1.7x Tele Converter Lens
200864	140547	WCON-07 .7x Wide Converter Lens
200713	125773	MCON-40 Macro Lens
200756	134607	CLA-4 Lens Adapter Tube
200858	140516	FL-20 TTL Hot Shoe Flash
200596	127654	FL-40 TTL Hot Shoe Flash
200663	131217	FC-CB02 Hot Shoe Cable to TTL Terminal Cable
200600	294066	Hot Shoe to PC Sync Adapter
200707	136168	FL-CB05 Hot Shoe to Hot Shoe TTL Cable (Off Camera)
200666	131149	FL-BK01 Flash Bracket
200830	139138	MAUSB-10 xD-Picture Card/SmartMedia USB Reader/Writer
200837	139512	MACF-10 xD-Picture Card/CompactFlash Adapter
200835	139145	MAPC-10 xD-Picture Card/SmartMedia PCMCIA/PC Card Adapter
200840	139084	xD-Picture Card 16MB
200841	139091	xD-Picture Card 32MB
200842	139107	xD-Picture Card 64MB
200843	139114	xD-Picture Card 128MB
200844	139565	xD-Picture Card 256MB
200784	295643	Digital Camera Gadget Bag
200776	136205	CB-USB4 Digital Camera USB Cable (replacement)
200667	132009	CB-AVC1 Digital Camera Audio/Video Cable (replacement)
200807	296060	C-Series 2-Year Extended Warranty

Memory Card Storage Capacity

Quality	Pixel Resolution	16MB xD-Picture Card™ (included)	256MB xD-Picture Card™
OIE: SHQ, HQ	3200 x 2400*	2, 8 shots	45, 136 shots
3:2 TIFF, SHQ, HQ	2288 x 1520	1, 6, 18 shots	25, 100, 290 shots
TIFF	2288 x 1712 to 640 x 480	1 – 16 shots	22 – 270 shots
SHQ, HQ	2288 x 1712	5, 16 shots	89, 261 shots
SQ1 (High, Normal)	2048 x 1536 to 1280 x 960	8 – 49 shots	140 – 799 shots
SQ2 (High, Normal)	1024 x 768, 640 x 480	26 – 165 shots	431 – 2663 shots
HQ	320 x 240 15 fps movie	33 sec. per sound movie	33 sec. per sound movie
SQ	160 x 120 15 fps movie	148 sec. per sound movie	148 sec. per sound movie

All still image capacity figures are approximated without audio. \*Optimum Image Enlargement resolution is interpolated from maximum optical resolution of 2288 x 1712.

Package Contents

- CAMEDIA C-750 Ultra Zoom Digital Camera
- 16MB xD-Picture Card™
- (4) Ni-MH Rechargeable Batteries and Charger
- Digital Camera Win/Mac USB Cable
- Video Cable
- Wrist Strap
- Quick Start Guide
- Printed Instruction Manual
- Warranty Card
- CD-ROM: CAMEDIA Master Software, Adobe Acrobat® Reader, Camera Reference Manual