

PRELIM

▲ Step-up

◆ New

With a 30 GB⁵ built-in Hard Disk Drive, the DCR-SR60 lets you capture up to 20 hours of video² or nearly 10,000 still pictures² in 1 Megapixel Digital Still Memory Mode. With on screen zoom and record buttons and a 2.7" LCD⁴ Wide Touch Panel SwivelScreen, you'll have complete control over every detail of your video.

▲ 1.0 Megapixel Advanced HAD™ CCD Imager; 1070K Gross

1/5.5" Advanced HAD™ (Hole Accumulation Diode) CCD with 690K (effective) video pixels provides stunning detail and clarity, for exceptional video (up to 520 lines of horizontal resolution) and still image performance. REalize great looking digital still images with 1,000K effective pixels.

— 12X Optical/800X Digital Zoom

The optical zoom helps to bring the action close up from far away. In addition, the Digital Zoom interpolation means that extreme digital zooming is clearer, with less distortion than previous types of digital zooms.

— Professional Quality Carl Zeiss® Vario-Tessar® Lens

Carl Zeiss lenses have an advanced optical multi-layer coating for increased contrast. This results in vivid image brilliance, true-to-life color saturation and perfect renditions of subtle tones.

◆ Handycam® Station

Simply placing the camcorder on the supplied Handycam Station cradle provides quick connections to a TV for viewing or a PC for editing and sharing, all while charging the battery so your camcorder is always ready to go.

▲ 2.7" Wide Touch Panel SwivelScreen™ LCD Display (123K Pixels)⁴

The 2.7" Wide (16:9) LCD screen provides excellent viewing clarity. The high resolution 123K pixel LCD screen rotates up to 270 degrees for multiple viewing angles providing sharp, detailed images for monitoring or playback, and the widescreen format makes shooting in 16:9 mode and composing shots even easier.

▲ Digital Still Memory Mode

Capture still images up to 1152x864 resolution, directly onto the internal 30GB Hard Disk Drive for easy transfer to PCs for emailing and printing via the computer.

▲ One Touch Wide Angle Shooting

Easily switch between 16:9 and 4:3 aspect ratios for shooting, with just the touch of a button.

▲ Progressive Shutter System

A mechanical shutter system that provides progressive scan performance while utilizing an interlaced scanning system. Digital still images will be sharp and clear with excellent definition.

— Super SteadyShot® Picture Stabilization System

An advanced version of Sony's SteadyShot® system that controls an even higher range of shake and vibration frequencies, to achieve an even higher level of smoothness without degradation of video like some other image stabilization systems.

▲ Analog Inputs

Record any analog NTSC source to digital via the analog inputs. Perfect for archiving analog tape recordings. This recorded videocan then be transferred to your computer for editing or duplicating onto a DVD for easy sharing.

— USB 2.0 Interface³

USB 2.0 interface provides an easy way to connect your Hard Disk Handycam Camcorder to the computer for fast transfer of video and still images to your computer for editing. The camcorder can also be used as an external storage device, convenient for archiving, storing and transporting your videos and still images.

◆ DVDirect™ Compatibility

The DVDirect system allows for easy transfer to a stand-alone DVD Burner via USB 2.0. The VRD-MC30 allows for easy transfer of video for DVD Burning. While the VRD-MC3 allows for seamless transfer of both Video and Still images for archiving on a DVD.

— Easy PC Backup

Easily back up your footage to your PC using the supplied software. The footage will be stored on your PC's hard drive for archiving purposes and viewing at a later time; the footage is stored by date allowing for quick access. In addition, only new footage is transferred to your PC each time you Backup your footage.

— One Touch DVD Burn

Easily burn a DVD copy of your footage using the supplied software. Simply connect you DCR-SR60 to your PC via the Handycam Station and supplied USB³ cable and press the One Touch DVD Burn button.

— HDD Smart Protection

A unique Shock Absorber protects the Hard Disk Drive from physical damage if the unit is dropped. When the 3G Sensor detects a drop (loss of gravity) the power to the Hard Disk Drive is turned off in order to prevent damage, during this time the DCR-SR60 remains powered on and recording video to the built-in buffer. Once the unit has recovered from the drop the buffer is then recorded to the Hard Disk Drive.

▲ Active Interface Shoe

Provides a location directly on the camcorder to which one may add optional accessories while providing power and two-way communication with those accessories.

ADDITIONAL FEATURES

- Super NightShot® Plus Infrared System
- Manual Focus
- On Screen Zoom and Record Buttons
- Program AE (Auto Exposure) Modes
- Picture Effects
- Fader Effects
- InfoLithium® Battery with AccuPower™ Meter System¹
- Battery Information
- Easy Handycam Button
- Tele Macro Function



WIDE LCD



Specifications

General

Imaging Device: 1/5.5" 1070K Gross Pixels CCD
Pixel Gross: 1070K
Recording Media: 30GB⁵ Hard Disk Drive
Recording and Playback Times: HQ: 7 hours, SP: 10 hours, LP 20 hours
Video Actual: 670K Pixels (16:9), 690K Pixels (4:3)
Still Actual: 746K Pixels (16:9), 1000K Pixels (4:3)

Audio

Dolby® Digital Output: N/A
Recording System: Dolby Digital AC3 (2 Channel)

Convenience

USB Streaming: N/A
SteadyShot® Image Stabilization: Yes (Super; Electronic)
Accessory Shoe: Yes, Active Interface Shoe
White Balance: Auto, Indoor, One-push, Outdoor
Memory Stick PRO™ Media Compatibility: N/A
Still Image Mode(s): JPEG
Minimum Illumination: 7 Lux (0 Lux with Super NightShot® Plus Infrared System)
Low Light Capability: Super NightShot® Plus

Inputs and Outputs

Analog Audio/Video Input(s): Yes (Multi A/V)
Analog Audio/Video Output(s): Yes (Multi A/V)
Digital Audio/Video Input(s): Yes (via USB)
Digital Audio/Video Output(s): Yes (via USB)
USB Port(s): Yes; 2.0 High Speed Compliant (Handycam Station)³
Component Video (Y/Pb/Pr) Output(s): N/A
Headphone Jack: N/A
Microphone Input: Yes (via Active Interface Shoe)
Remote Jack: Yes
S-Video Input(s): N/A
S-Video Output(s): Yes (via optional accessory)
HDMI™ Connection Output(s): N/A

Hardware

LCD: 2.7" (123K Pixels) Wide (16:9) Hybrid Touch Panel SwivelScreen™ LCD Display⁴
Lens Type: Carl Zeiss® Vario-Tessar®
Viewfinder: N/A
Docking Station: Yes; Handycam Station
Microphone: Yes (Built-in)

Optics/Lens

35mm Equivalent: 46-628.5mm (16:9 Camera Mode), 48-576mm (4:3 Camera Mode), 43.6-523.2mm (16:9 Memory Mode), 40-480mm (4:3 Memory Mode)
Aperture: f1.8-f2.5
Exposure: Yes; Touch Panel (24 steps)
Filter Diameter: 30mm
Focal Distance: 3.0 - 36mm
Focus: Full Range Auto/Manual (Touch Panel)

Progressive Shutter Mode: Yes
Shutter Speed: Auto, 1/4-1/4000 (AE Mode)
Optical Zoom: 12X
Digital Zoom: 800X
Resolution: 1MP

Power

Power Consumption: 2.8W/2.6W (LCD BL On/LCD BL Off)
Battery Type: InfoLithium® with AccuPower™ Meter System (NP-FP50)¹

Service and Warranty Information

Limited Warranty: 1 Year Parts; 90 Days Labor

Software

Operating System Compatibility: Microsoft® Windows® 2000 Professional, XP Home, XP Professional
Supplied Software: ImageMixer for Hard Disk Drive Handycam® Camcorder

Video

Video Recording System: MPEG2 (SD)
Analog-to-Digital Converter: Yes
Format(s) Supported: Non-Removeable Hard Disk Drive

Dimensions

Weight: 14oz. (390g) with supplied battery
Measurements: 2 3/4" x 2 7/8" x 4 5/8" (69 x 71 x 177mm)

Supplied Accessories

AC Power Adaptor/Camera Charger (AC-L25)
 InfoLithium® Rechargeable Battery (NP-FP50)
 Remote Commander® Remote Control (RMT-835)
 Handycam Station
 A/V Cable (Stereo)
 USB Cable
 ImageMixer for Hard Disk Drive Handycam® Camcorder (Application Software, Drivers and Handbook)

Optional Accessories

Starter Kit (ACC-FP71)
 Rechargeable InfoLithium® Batteries (NP-FP50/FP71/FP90)
 Travel Charger (BC-TRP)

UPC Code: 027242698970

1. Actual battery life may vary based on product settings, usage patterns and environmental conditions. Designed for use with compatible Sony InfoLithium® batteries.
 2. Image size and files size may vary based upon the type and complexity of the image recorded.
 3. Not all products with USB 2.0 connector may communicate with each other due to chipset variations.
 4. Viewable area measured diagonally
 5. 30GB means 30 billion bytes. Available storage capacity may vary and a portion of the memory is used for data management function.

© 2006 Sony Electronics Inc.
 Reproduction in whole or in part without written permission is prohibited. All rights reserved. Sony, AccuPower, Advanced HAD, DVDirect, Handycam, InfoLithium, like no other, NightShot, Remote Commander, SteadyShot and SwivelScreen are trademarks of Sony. Carl Zeiss and Vario-Tessar are trademarks of Carl Zeiss. PictBridge is a trademark of CIPA. Microsoft and Windows are registered trademarks of Microsoft Corporation. Macintosh is a registered trademark of Apple Computer, Inc. All other trademarks are property of their respective owners.
 Features and specifications subject to change without notice. Non-metric weights and measures are approximate.
 Screen Images Simulated

Please visit the Dealer Network for more information at www.sony.com/dn