DCR-TRV80

Digital Handycam® Camcorder

The DCR-TRV80 is the ultimate MiniDV Handycam® Camcorder, with a 2.0 Megapixel Advanced HAD™ CCD Imager, 3.5" Touch Panel LCD Screen, Networking Capability with BluetoothTM Technology and BIP (Basic Image Profile).



FEATURES

2.1 Megapixel (Gross) Advanced HAD™ CCD Imager



1/3.6" Advanced HAD™ (Hole Accumulation Diode) CCD imager with 1080K (effective) video pixels

provides excellent detail and clarity, for exceptional digital video performance. Realize unprecedented digital still images with 1920K (effective) pixels. The Megapixel technology enhances your digital videos (530 lines of horizontal resolution) and digital photography performance.

MiniDV Recording

MiniDV digital recording format delivers 3X the color bandwidth of VHS and lower signal to noise ratio compared to analog formats, providing stunning video performance comparible to DVD.

Network Capability with Bluetooth™ Technology

™ Connect the camera to the Internet for PC-free networking. The Network function allows you to browse the web, send and receive email messages (with attachments) or upload digital still images and MPÉG1 movies stored on Memory Stick® media to Sony's ImageStation® storage site. Connect to the Internet with the optional hardwired USB Network adapter (analog phone line to USB) or wirelessly through Bluetooth™ technology to compatible Bluetooth modems or cellular phones (Compatible ISP required). AOL compatible: AOL members can enjoy networking features listed above with the exception of receiving email. The BIP (Basic Image Profile) feature allows you to "push" or exchange images wirelessly to other BIP compatible devices (i.e. printers, computers, and camcorders) for easy transfer without a cabled connection.

Professional Quality Carl Zeiss® Vario-Sonnar® T*Lens

Carl Zeiss lenses have an advanced optical multi-layer coating offering less glare and flare with increased contrast. This results in vivid image brilliance, true-to-life color saturation, and perfect renditions of subtle tones.

► STEP-UP FEATURE

10X Optical/120X Precision Digital Zoom

The optical zoom helps to bring the action up close from far away. In addition, the digital zoom interpolation means that extreme digital zooming is clearer, with less distortion than previous types of digital zooms.

>3.5" SwivelScreen™ Touch Panel LCD Display (184K Pixels) with Stylus



Provides excellent viewing clarity with improved Panel resolution. The 184K pixel

LCD display makes images sharp and detailed during playback or when monitoring recording. The "On Screen" touch panel LCD system allows you to navigate through the camera's menu system by touching the LCD screen using the supplied stylus.

Precision Color Viewfinder (180K Pixels)



Increased pixel count provides more detail and clarity of video subjects.

USB Streaming



Stay connected with family and friends by broadcasting live video with audio, via the

Internet with the USB interface. You can even playback your favorite recorded scene stored on tape. It's like having your own web camera or video conferencing system.

Digital Still Memory Mode with Memory Stick® Media



Digital Still Memory Mode captures high quality Megapixel still images at up to 1600 x 1200 resolution

directly to Memory Stick media. Images are stored in a JPEG format providing easy transfer to PCs for emailing, printing, or sharing with family and friends. 8MB Memory Stick media is supplied.

MPEG Movie EX Mode



Unlike earlier MPEG1 Movies, MPEG Movie EX will allow you to record uninterrupted to the

capacity of the Memory Stick media. For example a 128MB Memory Stick will record up to 85 minutes of non-stop MPEG1 video.

Manual Focus/Zoom Ring

Provides a sharper focus in low or nolight situations. By setting the focus to manual the focus ring can be turned to achieve a more accurate focus in dark situations.

Expanded Focus Indicator

While using the manual focus ring, the camera automatically adjusts to 2x magnification, allowing for extremely accurate focus adjustment.

Progressive Shutter System

A mechanical shutter system that provides Progressive Scan performance while utilizing an interlaced scanning system. Digital still images will be sharp and clear with excellent definition.

Intelligent Pop-Up Flash

Provides the appropriate amount of flash for optimum brightness and color accuracy in virtually any lighting condition when shooting still images.

i.LINK** DV Interface (IEEE1394)



DIGITAL VIDEO A high speed bi-directional digital video/audio communication between two compatible devices

equipped with a IEEE1394 interface, including camcorders, digital VTRs, capture cards and PCs.

Super SteadyShot Picture Stabilization System



An advanced version of Sony's SteadyShot® System that controls an even higher range

of shake and vibration frequencies to achieve an even higher level of smoothness without degradation of video like some other image stabilization systems.

Super NightShot Infrared System and Color Slow Shutter



With Sony's NightShot® infrared system, capture video in total OLUX darkness (0 lux) up to 10 feet away.

Super NightShot 0 Lux recording mode automatically adjusts the shutter speed to increase picture brightness and clarity. Color Slow Shutter mode allows you to record in low light situations with full color detail by slowing down the shutter speed.

ADDITIONAL FEATURES

12-Bit/16-Bit PCM Digital Stereo 14 Bit DXP A/D Conversion Analog-to-Digital Conversion with Pass-Through **Battery Information** Digital Picture Effects Digital Program Editing **EXIF 2.2**

Fader Effects Hologram AF Low Light Laser

Assist Focus System

InfoLithium® Battery with AccuPower™ Meter System Intelligent Accessory Shoe Pixela ImageMixer CD-ROM Software

Playback Zoom Program AE (Auto Exposure)

Modes

Simultaneous Record Mode Stamina® Battery Power Management System

SPECIFICATIONS

Imaging Device: 1/3.6", 2110K Gross Pixels, Advanced HAD™ CCD

Video Actual: 1080K Pixels Still Actual: 1920K Pixels

F: 1.8-2.1

Focal Distance: 4.5-45mm

35mm Conversion: 52-520mm (Camera Mode) 39-390mm (Photo Mode)

Filter Diameter: 37mm Optical Zoom: 10X Digital Zoom: 120X

Focusing: Full Range Auto/Manual (Touch Panel) Minimum Illumination: 7 Lux (0 Lux with NightShot® Infrared System)

NightShot Infrared System: Super NightShot, Color Slow Shutter

Shutter Speed: 1/4-1/4000 (Program AE Mode) Memory Mode: Yes, 1600 x 1200, 640 x 480

MPEG Movie EX Mode: Yes

Viewfinder: Precision Color (180K Pixels)

LCD: 3.5" Color (184K Pixels) Accessory Shoe: Yes (Intelligent) Portable Printer Capable: Yes

Video Input/Output: Yes/Yes (Mini and S-Video)

Audio Input/Output: Yes/Yes

i.LINK® DV Interface (IEEE 1394): Yes

USB Terminal: Yes

Memory Stick PRO™ Media Compatibility: Tested to support up to 1GB media capacity; does not support high speed transfer function; does not support Access Control security function

USB Streaming: Yes

Headphone Jack: Yes (Mini, Stereo)

Mic-Input: Yes (Stereo)

White Balance: Auto, Outdoor, Indoor, Hold Exposure: Yes/Touch Panel (24 Step)

Software OS Compatibility: Microsoft® Windows® 98SE, 2000, Me,

XP; Macintosh® 8.5.1 - 9.1*3

Power Consumption (VF/LCD/VF+LCD): 4.1W/ 5.1W/ 5.4W **Dimensions (WHD):** 2 ⁷/8" x 3 ³/4" x 6 ³/4" (73mm x 93mm x 169mm)

Weight: 1 lb 9 oz (720g) without Tape and Battery

Supplied Accessories: AC-L15 Power Adapter/In Camera Charger, NP-FM50 InfoLithium Rechargeable Battery, 8MB Memory Stick® Media, RMT-811 Wireless Remote Commander® Remote, 2 AA Batteries, A/V Cable, Lens Cap, Shoulder Strap, USB Cable, LCD Cleaning Cloth, Stylus, CD-ROM

w/USB Driver (Pixela ImageMixer Ver. 1.5)

SONY

Sony Electronics Inc. 16765 West Bernardo Drive San Diego, CA 92127 www.sony.com/di

WORRY FREE™ BATTERY LIFE

Battery* (Fully charged)	Rec Time VF/LCD/VF+LCD	Playback Time LCD On/Off			
NP-FM30	70/55/50 min	85/125 min			
NP-FM50	120/95/90 min	140/200 min			
NP-FM70	250/200/190 min	295/415 min			
NP-QM71D	290/230/220 min	340/485 min			
NP-FM90	380/305/285 min	450/630 min			
NP-QM91D	445/350/330 min	520/725 min			
*Results may vary depending upon conditions					

MEMORY MODE



Ν	Media	k° Fine/Std 1600 x 1200	Fine/Std 640 x 480	Memory Stick PRO™ Media	Fine/Std 1600 x 1200	Fine/Std 640 x 480	
	8MB	8/18	50/120	256MB	235/540	1400/3550	
	16MB	16/37	96/240	512MB	480/1100	2850/7200	
	32MB	32/75	190/485	1GB	980/2250	5900/14,500	
	64MB	65/150	390/980				
	128MB	130/300	780/1970				/



MPEG MOVIE EX MODE

h=hour, m=minute, s=second

Me	mory Stick® Media	Email Mode (160 x 112)	Presentation Mode (320 x 240)	Memory Stick PRO* Media	M Email Mode (160 x 112)	Presentation Mode (320 x 240)
	8MB	5m 20s	1m 20s	256MB	2h 50m 40s	42m 40s
	16MB	10m 40s	2m 40s	512MB	5h 41m 20s	1h 25m 20s
	32MB	21m 20s	5m 20s	1GB	11h 22m 40s	2h 50m 40s
	64MB	42m 40s	10m 40s			
1	.28MB	1h 25m 20s	21m 20s			

OPTIONAL ACCESSORIES

AC-SQ950D AC Quick Charger for Super Quick Batteries

NP-QM71D/91D Super Quick High Capacity InfoLithium Batteries

NP-FM50/70/90 High Capacity InfoLithium Batteries

LCS-VA1 Carrying Case MSA-16/32/64/128 Memory Stick® Media

MSA-128SZ Memory Stick® Select Media

MSX-256/512/1GB Memory Stick PRO™ Media

HVL-IRH2 NightShot Infrared Light HVL-S3D Video Light

VCT-870RM Remote Control Tripod **UNA-EN1** Ethernet Adaptor UNA-PSTN Analog Phone Line

Adaptor

BTA-NW1A Bluetooth Modem Adaptor

©2003 Sony Electronics Inc.

Reproduction in whole or in part without written permission is prohibited. All rights reserved. Sony, AccuPower, Advanced HAD, Handycam, i.LINK, ImageStation, InfoLithium, Memory Stick, Memory Stick PRO, NightShot, Remote Commander, Stamina, SteadyShot, SwivelScreen and Worry Free are trademarks of Sony. Carl Zeiss and Vario-Sonnar are trademarks of Carl Zeiss. Bluetooth and logos are trademarks of Bluetooth. Microsoft and Windows are registered trademarks of Microsoft Corporation. Macintosh is a trademark of Apple Computer, Inc.

All other trademarks are property of their respective owners. Features and specifications subject to change without notice. Non-metric weights and measures are approximate

 $^{^{\}star}$ i.LINK is a trademark of Sony, used only to designate that a product contains an IEEE1394 connector. All products with an IEEE1394 connector may not communicate with each other.

^{**} Not compatible with USB Streaming.