



EPSON PowerLite[®] 735c

Wireless Presentation at its Best

The industry's lightest wireless presentation solution to date, the 4.4 lb EPSON PowerLite® 735c offers remarkable control flexibility with 802.11b wireless technology. Designed to facilitate quick setups and easy network management, this 2000 ANSI lumen, ultra portable projector also offers remote diagnostics and monitoring.

In addition, its newly improved EasyMP[™] technology enables convenient PC-free presentations with incredible PowerPoint® functionality and brilliant high-speed transitions.

With EPSON 3-LCD technology and XGA resolution, this full-featured performer delivers exceptional image quality in any situation.

Newly improved EPSON EasyMP

- PC-free presenting
- More animation and PowerPoint functionality than ever before
- · High-speed image transfers

Convenient connectivity options, including wireless capability!

- No video cable required Laptop and projector can be positioned independently for optimal viewing and control.
- 802.11b wireless technology (WiFi[™] certified)
- · Two wireless modes for individual or LAN users
- · Easy administration via web browser access
- Simple Network Management Protocol (SNMP) for easy network management and maintenance
- · Control flexibility displays images on up to four projectors simultaneously
- Security features safeguards the display screen for uninterrupted presentations

high

Incredible brightness-to-weight ratio!

- · 2000 brilliant ANSI lumens
- · Weighs just 4.4 lb

Superior image quality

- Three 0.9" high-aperture EPSON LCDs with Micro Lens Array, for rich color saturation across the screen
- XGA (1024 x 768) resolution for sharp, vivid detail
- 400:1 contrast ratio for blacker blacks and whiter whites

Easy setup and operation

- · Easy-to-use remote control that's stored within the projector
- · Exclusive auto keystone correction
- · Color-coded VGA cables and connectors
- HDTV-ready
- Optical zoom
- Start Here Kit gets first time users projecting in just minutes

Renowned EPSON service and support (free for the duration of the warranty)

- Comprehensive two-year warranty
- 90-day bulb warranty for added dependability
- · EPSON Road Service Program provides a replacement projector, typically within 24 hours
- EPSON PrivateLine[™] dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday - Friday (Calls are answered live, typically in about a minute.)
- · International warranty in over 45 countries



EPSON PowerLite 735c Specifications

Projection System	EPSON original LCD prism technology		
Projection Method	Front/rear/ceiling mount		
LCD			
Size	0.9"		
Driving Method	EPSON Poly-Silicon TFT Active Matrix		
Pixel Number Native Resolution	786,432 dots x3 (1024 x 768) LCDs XGA		
Aspect Ratio	4:3 (supports 16:9, 5:4)		
Pixel Arrangement	Stripe		
Projection Lens			
Туре	Manual: zoom/focus		
F-number f-number	1.9 to 2.1 31 – 36mm		
Zoom ratio	1:1.16		
Lamp			
Туре	150W UHE		
Life (typical)	1500H (can last about 5 yrs. based on		
	6 hours/week x 50 weeks/year)		
Screen Width Ratio: (dista			
Screen Size (projected dist			
Keystone Correction	+/- 15 degrees		
Brightness (typical)	2000 ANSI lumens		
Contrast Ratio	400:1		
Brightness Uniformity (typ	bical) 85%		
Color Reproduction	24 bit; 16.7ml		
Sound Output	1W		
Operating Temperature	5°C to 35°C (41°F to 95°F)		
Power Supply Voltage	100-120V, 200-240V +/-10%, 50/60Hz AC		
Power Consumption	225W / 5.5W at sleep mode		
Maximum Dimensions D x	x W x H		
(includes lens and feet)	7.5" x 10.9" x 3.1"		
(excludes lens and feet)	7.5" x 10.9" x 2.7"		
Weight	4.4 lbs/1.9kg		
Fan Noise	39db		
Effective Scanning Freque	ncy Range		
Pixel Clock	13.5MHz to 162MHz		
Horizontal	15KHz to 92KHz 50Hz to 85Hz		
Vertical	50HZ 10 85HZ		
Remote Control Features	Keystone, special effects, source selection,		
reatures	power, color mode, page up/down,		
	volume, presets		
Or contine Areals			
Operating Angle	+/_ 30° horizontally +/_ 15° vertically		
	/_ To vertically		
Operating Distance	20ft (6m)		
RGB			
Diaplay porformer-	Analog RGB I/O		
Display performance Native	1024 x 768		
Resize	1600 x 1200		
	1280 x 1024		
	800 x 600		
	640 x 480		
Input terminal			
Video	Mini D-sub 15pin x 1		
Audio	Stereo mini jack		

THE WORLD LEADER IN

HIGH PERFORMANCE PROJECTORS

EPSON

www.epson.com

Card I/O PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, compatibility SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive" Other Wireless LAN card (standard accessory only) Wired LAN card Video I/O 550 TV Line Input signal NTSC/NTSC4.43/PAL/M-PAL/ N-PAL/PAL60/SECAM N-PAL/PAL60/SECAM Input terminal Video Video Mini DIN Component Video: Mini D-sub 15pin (in common with Analog RGB connector); Video RGB: Mini D-sub 15pin (in common with Analog RGB connector) Audio Stereo mini jack (in common with Analog RGB audio jack) Audio signal 500m Vrms/47Kohm VID USB type B x 1 (for mouse, keyboard control and RS-232 communication)
PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive" Other Wireless LAN card (standard accessory only) Wired LAN card Video I/O 550 TV Line Input signal NTSC/NTSC4.43/PAL/M-PAL/ N-PAL/PAL60/SECAM N-PAL/PAL60/SECAM Input terminal Video Video HDTV: 480i, 480p, 720p,1080i Component Video: RCA x 1 S-Video: Mini DIN Component Video: Mini D-sub 15pin (in common with Analog RGB connector); Video RGB: Mini D-sub 15pin (in common with Analog RGB connector) Audio Stereo mini jack (in common with Analog RGB audio jack)
PC card slot PC card slot Memory card compatibility Other Other PCMCIA type I/II Compact Flash, Smart Media, Memory Stick, SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive" Other Wireless LAN card (standard accessory only) Wired LAN card Video I/O Display performance S50 TV Line Input signal Input terminal Video HDTV: 480i, 480p, 720p,1080i Composite Video: RCA x 1 S-Video: Mini D-sub 15pin (in common with Analog RGB connector); Video Audio Stereo mini jack
PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, compatibility SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive" Other Wireless LAN card (standard accessory only) Wired LAN card Video I/O 550 TV Line Input signal NTSC/NTSC4.43/PAL/M-PAL/ N-PAL/PAL60/SECAM NDV: 480i, 480p, 720p,1080i
PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, compatibility SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive" Other Wireless LAN card (standard accessory only) Wired LAN card Video I/O 550 TV Line Input signal NTSC/NTSC4.43/PAL/M-PAL/
PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, compatibility SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive" Other Wireless LAN card (standard accessory only) Wired LAN card Video I/O
PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, compatibility SD, MMC, 3.3 volts type ATA Flash card, 5 volts type ATA Flash card, IBM MicroDrive** Other Wireless LAN card (standard accessory only)
PC card slot PCMCIA type I/II Memory card Compact Flash, Smart Media, Memory Stick, compatibility SD, MMC, 3.3 volts type ATA Flash card,

Warranty

Standard two year limited warranty, 2-year international warranty, 90-day lamp warranty, EPSON Road Service Program and EPSON PrivateLine dedicated toll-free support (U.S. and Canada only)

Supplied Accessories

Power cable, card type remote control with lithium battery, computer cable HD15/HD15, RCA video cable, USB mouse cable, Wireless LAN card, Start Here Kit, CD-Rom, soft carrying case

		-	
Droduct	Accessory	Dart	Numbore

Product/Accessory Part Numbers	
EPSON PowerLite 735c Projector	V11H103020
Replacement lamp	V13H010L18
Samsonite wheeled soft case (16.75" x 15" x 9")	ELPKS24
Soft shoulder bag	ELPKS31
Notebook/projector soft shoulder bag	ELPKS32
ATA wheeled hardshell notebook/projector case	ELPKS42
Ceiling mount	ELPMB37
Suspension adapter	ELPMBAPL
False ceiling plate	ELPMBFCP
Distribution amplifier	ELPDA01
Component video cable	ELPKC19
S-video cable	ELPSV01
Mac adapter set	ELPAP01
50" portable projection screen	ELPSC06
60" portable pop-up screen	ELPSC07
80" portable pop-up screen	ELPSC08
High resolution document imager	ELPDC02
High resolution document camera	V12H064020
Kensington security lock	ELPSL01
Support–The Epson Connection [™]	
Pre-Sales Support U.S. and Canada	800-463-7766
Automated Technical Support	800-922-8911
Internet Web Site	www.epson.com
Presenters ONLINE"	presentersonline.com

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806 Epson Canada, Ltd.

3771 Victoria Park Ave, Toronto, Ontario M1W 3Z5

Epson Latin America 6303 Blue Lagoon Drive, Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON is a registered trademark and EasyManagement is a trademark of Seiko Epson Corporation. PowerLite is a registered trademark, SizeWise is a trademark and Epson Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2003 Epson America, Inc. CPD-15540 25K 2/03 CL Printed on Recycled Paper