

DIGITAL CAMERA

FinePix A202

New

2.0M
EFFECTIVE
PIXELS

Actual size



Discover Pure Digital Excitement: The FinePix A202

- ▶ *High-quality images with 2.0 million effective pixels*
- ▶ *Compact, stylish design*
- ▶ *Up to 2.5X digital zooming (in 640 × 480-pixel mode)*
- ▶ *Accepts new xD-Picture Card for image storage*
- ▶ *Movie recording capability*
- ▶ *User-friendly menus on the built-in LCD monitor*
- ▶ *Automatic exposure control and auto white balance*
- ▶ *World leading energy-saving technology (long life even on two AA batteries)*

FinePix

The Ultra-easy Digital Camera That Makes Great Pictures a Snap



Superb image quality

With its 2.0 million effective pixels and quality Fujinon optics, the FinePix A202 delivers sharp detail and lifelike color.

Pocket-sized design

Weighing only 132g (without batteries) and measuring just 100 x 65mm, the FinePix A202 makes a perfect fit in your pocket or your hands.

Movie recording function

Use the FinePix A202's movie recording feature to make your own mini-videos up to 80 seconds long*.

* 160 x 120-pixel mode, no sound

Quick, easy operation

The camera comes with two AA alkaline batteries and a 16MB xD-Picture Card, so you can start taking pictures right away. Simply slide the power switch to open the lens cover. The camera is immediately ready to shoot – just press the shutter button and start enjoying digital photography.

Versatile 2.5X digital zooming

The FinePix A202's lens offers an easy-to-use focal length equivalent to 36mm on a 35mm camera. Plus the 2.5X digital zoom lets you move right in on the action.

Long battery life

Designed to save on power, the FinePix A202 lets you enjoy up to 270 shots* on a single pair of AA alkaline batteries.

* With the LCD turned off and using the flash half of the time

xD-Picture Card – a new standard storage media

The FinePix A202 is designed around the xD-Picture Card, the new standard in ultra-compact digital storage media. The introduction of compatible USB card reader and PC/CompactFlash™ card adapters means effortless PC data-transfer and other versatile advantages.


Windows XP Compatible

The FinePix A202 and included USB driver software are certificated as "Designed for Microsoft® Windows® XP". Both are also fully functional with Windows 98SE/2000/ME and the Mac OS.



Specifications

DIGITAL CAMERA FinePix A202

Number of effective pixels*	2.0 million pixels					
CCD sensor	1/2.7-inch square pixel CCD with RGB filter (Number of total pixels: 2.11 million pixels)					
Image file size	1600 x 1200/1280 x 960/640 x 480 pixels					
File format	Still image: JPEG (Exif Ver. 2.2**)/Movie: AVI (Motion JPEG) Design rule for Camera File system compliant/DPOF-compatible 					
Storage media	xD-Picture Card (16MB to 128MB)					
Number of images/recording time						
Modes	Still image			Movie		
Image quality mode displayed	2M (Fine)	2M (Normal)	1M	0.3M	320	160
Number of recorded pixels	1600 x 1200	1280 x 960	640 x 480	320 x 240	160 x 120	
DPC-16 (16MB)	25	39	49	122	Approx. 94 sec.	Approx. 5.0 min.
DPC-32 (32MB)	50	79	99	247	Approx. 191 sec.	Approx. 10.1 min.
DPC-64 (64MB)	101	159	198	497	Approx. 6.4 min.	Approx. 20.2 min.
DPC-128 (128MB)	204	319	398	997	Approx. 12.9 min.	Approx. 40.6 min.
Data size and number of available shots will vary slightly depending on the type of subject.						
Lens	Fujinon optical fixed lens, equivalent to 36 mm on a 35 mm camera					
Focus distance	Normal: Approx. 80 cm/2.6 ft. to infinity Macro: Approx. 8 to 13 cm/3.1 in. to 5.1 in.					
Aperture	F4.6/F9.5 (Automatically selected)					
Exposure control	64-zone TTL metering, Programmed AE (Exposure compensation in manual mode)					
Sensitivity	Equivalent to ISO 100					
Shutter speed	1/2 to 1/1,000 sec. (combined with mechanical shutter)					
White balance	Automatic (7 positions selectable in Manual mode)					
Flash	Auto flash using flash control sensor Flash mode: Auto, Red-eye Reduction, Forced Flash, Suppressed Flash, Slow Syncro Effective range: 0.8 – 3.0 m/2.6 in. – 9.8 ft.					

LCD monitor	1.5-inch D-TFD (55,000 pixels)
Interface	USB
Power source	2x AA alkaline/Ni-MH batteries or AC power adapter (optional)
Dimensions	98.5 (W) x 64.5 (H) x 40.5 mm(D)/3.9 (W) x 2.5 (H) x 1.6 (D) in.
Weight	Approx. 132 g/4.7 oz. (excluding batteries and media)
Other Functions	
<i>Digital zoom</i>	2.5X (640 x 480 mode), 1.25X (1280 x 960 mode)
<i>Movie recording</i>	320 x 240 pixels, 10 frames/sec, up to 20 sec, without sound 160 x 120 pixels, 10 frames/sec, up to 80 sec, without sound
<i>Playback</i>	Single Frame (with max. 10X Playback Zoom)/9 Multi-frame
<i>Internet-conferencing</i>	Webcam function with "PictureHello"
<i>Others</i>	POWER SAVE mode, Self-timer, DPOF
Accessories included	<ul style="list-style-type: none"> • 16MB xD-Picture Card • 2 AA-size alkaline batteries • Hand strap • USB cable • CD-ROM: <ul style="list-style-type: none"> USB Driver, FinePixViewer, DP Editor, Apple Quick Time 5.0, ImageMixer VCD for FinePix
Optional accessories	XD-Picture Card (DPC-16, DPC-32, DPC-64 and DPC-128), Image Memory Card Reader DPC-R1, PC Card Adapter DPC-AD, AC Power Adaptor AC-3V, Battery Charger with Battery BK-NH (Charged in approx. 2 hours, with Euro type or UK type plug), Rechargeable Battery 2HR-3UF (2x AA-type Ni-MH)

* Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

** Exif 2.2 is a newly revised digital camera file format that contains a variety of shooting information for optimal printing.

Exif Print

Specifications are subject to change without notice.

xD-Picture Card and all other trademarks are the property of their respective holders.

For more information on the full range of Fujifilm digital products, please visit our Website: <http://home.fujifilm.com>



FUJIFILM

FUJI PHOTO FILM CO., LTD.

26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN

Ref. No. EB-212E (SK-02-08-DT-MW) Printed in Japan © 2002 Fuji Photo Film Co., Ltd.