



COOLPIX

At the heart of the image



- 7.1 megapixels
- 3x zoom
- 2.5-inch LCD
- VR image stabilization
- High response
- ISO 2000 capability



COOLPIX S500

www.nikon-coolpix.com

Stylish elegance meets advanced performance.

High-quality, compact stainless steel body

From the solid feel and comfortable wrap-around grip of its ultra compact stainless steel body to its large, easy-access control buttons and 2.5-inch high-resolution LCD monitor, the COOLPIX S500 is a joy to carry and to take pictures with.



High response

All functions are optimized for immediate response, freeing you to capture special moments as you experience them. The COOLPIX S500

powers up within 0.6 seconds, and the shutter releases in 0.005 seconds.

VR image stabilization

Nikon's optical lens shift VR (Vibration Reduction) system compensates for camera shake to produce clearer, sharper results in lower light or unsteady conditions. Active full time, VR's stabilizing effects also aid in smooth, easy framing and shooting.



ISO 2000 capability

Light sensitivity range up to ISO 2000 with manual control or auto control (up to ISO 1000) creates new opportunities to take sharper, more natural looking photos in lower lighting conditions, or to capture fast-moving subjects with outstanding clarity.

Anti-Shake button

One press of the button simultaneously activates the High-ISO, lens shift VR and BSS (Best Shot Selector) features of Anti-Shake mode for clearer results in low light or when zoomed in for close-ups.



Anti-Shake button

Other features

- Large 2.5-inch 230,000-dot LCD monitor with anti-reflection coating
- One-touch portrait button
- Face-priority AF
- In-Camera Red-Eye Fix
- D-Lighting

COOLPIX S500

VR image stabilization

Better pictures in lower light

Simply better portraits

Silver

Urban Black

Nikon COOLPIX S500 Specifications

Effective pixels:	7.1 million
Lens:	3x Zoom-Nikkor; 5.7-17.1mm (35mm [135] format picture angle: 35-105mm); f/2.8-4.7; 5 elements in 5 groups; Digital zoom: up to 4x (35mm [135] format picture angle: 420mm)
Focus range (from lens):	50cm (1 ft. 8 in.) to infinity (∞), Macro close-up mode: 15cm (5.9 in.) to infinity (∞)
Monitor:	2.5-in., 230,000-dot, TFT LCD with anti-reflection coating
Storage media:	Internal memory (approx. 26 MB), SD memory cards
ISO sensitivity:	ISO 50, 100, 200, 400, 800, 1600, 2000, Auto (auto gain ISO 50-1000)
Power sources:	Rechargeable Li-ion Battery EN-EL10 (supplied), AC Adapter EH-62D (optional)
Battery life:	Approx. 180 shots with EN-EL10 battery (based on CIPA standard)
Dimensions (WxHxD):	Approx. 88 x 51 x 22 mm (3.5 x 2.0 x 0.9 in.) excluding projections
Weight:	Approx. 125 g (4.4 oz.) without battery and SD memory card

PictureProject System Requirements

- OS:** **Macintosh:** Mac® OS X version 10.3.9, 10.4.x
Windows: Windows® Vista (32bit), Windows® XP Home Edition/Professional, Windows® 2000 Professional pre-installed models
- Note:** CD-ROM drive required for installation. Only built-in USB ports are supported

Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh® and QuickTime® are either registered trademarks or trademarks of Apple Computer Inc. in the United States and/or other countries. The SDHC logo is a trademark. PictBridge is a trademark. D-Lighting technology is provided by Apical Limited. Products and brand names are trademarks or registered trademarks of their respective companies. The FotoNation logo is a trademark. Image on LCD shown in this brochure is simulated. Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. February 2007 ©2007 NIKON CORPORATION



WARNING TO ENSURE CORRECT USAGE, READ MANUALS CAREFULLY BEFORE USING YOUR EQUIPMENT. SOME DOCUMENTATION IS SUPPLIED ON CD-ROM ONLY.



NIKON CORPORATION

Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku
 Tokyo 100-8331, Japan
<http://nikonimaging.com/>

Nikon Hong Kong Ltd. Suite 1001, 10/F Cityplaza One, 1111 King's Road, Taikoo Shing, Hong Kong www.nikon.com.hk
Nikon Singapore Pte. Ltd. No. 80 Anson Road, Fuji Xerox Towers, #10-01/02, Singapore 079907 www.nikon.com.sg
Nikon (Malaysia) Sdn. Bhd. 11th Floor, Block A, Menara PKNS, No. 17, Jalan Yong Shook Lin, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia www.nikon.com.my
NIKON AUSTRALIA PTY LTD. Unit F1, Lidcombe Business Park, 3-29 Birnie Avenue, Lidcombe NSW 2141, Australia www.nikon.com.au