

Canon

DIGITAL IXUS

Imagine with your IXUS.



DIGITAL
IXUS 500



DIGITAL
IXUS 430



DIGITAL
IXUS II s

A New Level of Picture-Taking Excellence

- ✕ 5.0 megapixel CCD
- ✕ 3x optical zoom lens
- ✕ 4.1 x digital zoom
- ✕ 9-point AiAF

5.0
MEGAPIXEL

9
POINT
AIAF



DIGITAL IXUS 500

● Specifications

LENS Focal Length 7.4(W) - 22.2(T)mm (35mm film equivalent: 36-108mm) **LCD MONITOR** 1.5 inch. LTIPS TFT color LCD (Approx. 11.8K pixels) **WHITE BALANCE** Auto, pre-set (Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H), custom **SHUTTER SPEEDS** 15 - 1/2000 sec. **SHOOTING MODES** Auto, manual, stitch assist and movie **CONTINUOUS SHOOTING** Approx. 2.2 shots / sec. (Large/Fine, LCD monitor off) **RECORDING MEDIA** CompactFlash™ (CF) Card (Type I) **DISPLAY LANGUAGES** 12 Types **INTERFACE** USB (mini-B, PTP) Audio / Video output (NTSC/PAL) **POWER SOURCE** Rechargeable battery NB-1LH/NB-1L **DIMENSIONS** (WxHxD) 87.0 X 57.0 X 27.8mm (excluding protrusions) **WEIGHT** approx. 185 g (Camera body only)

Pocket Size
Small

IXUS 430



- ✕ 4.0 megapixel CCD
- ✕ 3x optical zoom lens
- ✕ 3.6x digital zoom
- ✕ 9-point AiAF

● Specifications

LENS Focal Length 7.4(W) - 22.2(T)mm (35mm film equivalent: 36-108mm) **LCD MONITOR** 1.5 inch. LTPS TFT color LCD (Approx. 11.8K pixels) **WHITE BALANCE** Auto, pre-set (Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H), custom **SHUTTER SPEEDS** 15 - 1/2000 sec. **SHOOTING MODES** Auto, manual, stitch assist and movie **CONTINUOUS SHOOTING** Approx. 2.5 shots / sec. (Large/Fine, LCD monitor off) **RECORDING MEDIA** CompactFlash™ (CF) Card (Type I) **DISPLAY LANGUAGES** 12 Types **INTERFACE** USB (mini-B, PTP) Audio / Video output (NTSC/PAL) **POWER SOURCE** Rechargeable battery NB-1LH/NB-1L **DIMENSIONS** (WxHxD) 87.0 X 57.0 X 27.8mm (excluding protrusions) **WEIGHT** approx. 185 g (Camera body only)



Trendy & Stylish DIGITAL IXUS

- ✕ 3.2 megapixel CCD
- ✕ 2x optical zoom lens
- ✕ 3.2x digital zoom
- ✕ 9-point AiAF



3.2
MEGAPIXEL

9
POINT
AIAF

DIGITAL IXUS II s

● Specifications

LENS Focal Length 5.4(W) - 10.8(T)mm (35mm film equivalent: 35-70mm) **LCD MONITOR** 1.5 inch. LTPS TFT color LCD (Approx. 11.8K pixels) **WHITE BALANCE** Auto, pre-set (Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H), custom **SHUTTER SPEEDS** 15 - 1/1500 sec. **SHOOTING MODES** Auto, manual, stitch assist and movie **CONTINUOUS SHOOTING** Approx. 2.2 shots / sec. (Large/Fine, LCD monitor off) **RECORDING MEDIA** SD memory card **DISPLAY LANGUAGES** 12 Types **INTERFACE** USB (mini-B, PTP) Audio / Video output (NTSC/PAL) **POWER SOURCE** Rechargeable battery NB-3L **DIMENSIONS** (WxHxD) 85.0 X 56.0 X 23.9mm (excluding protrusions) **WEIGHT** approx. 165 g (Camera body only)

Direct Printing and Direct Transfer



Print/Share Button

Connect your Digital IXUS to any compatible printers, set to the Playback mode and hit the Print/Share button to get your prints.



ID Prints

For a full page of ID photos, connect your Digital IXUS to a CP printer, crop your recorded image to the required size and print.


Easy Printing



Direct Transfer

Connect your Digital IXUS to any Windows compatible PC, set to the Playback mode and hit the Print/Share button, images will be transferred to your PC* directly.

* Require installation of camera driver and dedicated software. Camera driver is not required for Windows XP.



Movie Prints

Print your favourite movie clips sequentially with a CP printer.

Other Great Features



DIGIC

- Proprietary imaging processor for high speed processing, colour fidelity and low noise.



Photo Effects Mode

- Choose from Vivid or Neutral Colour, Sepia (antique look), Black & White or Low Sharpening to suit your taste and your subject.



Intelligent Orientation Sensor

- Automatically rotates and displays vertical shots in proper orientation during playback for easy viewing and editing.



3 Minute Movie Mode

- Shoot up to 3 full minutes of motion with sound.

Accessories

- Canon Digital IXUS models are supplied with complete software and cables for downloading, storing, editing your photos and motion JPEG video clips.

- Optional underwater cases protect your camera from sand, snow, rain and even allow you to snorkel or scuba dive to a depth of 40 meters.



Waterproof case WP-DC800
(for IXUS 500 & IXUS 430)



Waterproof case WP-DC10
(for IXUS IIs)



Asia Regional Headquarters:
Canon Hongkong Co., Ltd.
9/E, The Hong Kong Club Building,
3A Chater Road, Central, Hong Kong
Website: www.canon-asia.com

Canon Singapore Pte. Ltd.
1 HarbourFront Avenue #04-01,
Keppel Bay Tower, Singapore 098632



CompactFlash™ is a trademark of SanDisk Corporation. SD is a trademark. Microsoft and Windows are registered trademarks of Microsoft Corporation in the USA and other countries. All other trademarks are acknowledged.

All data are based on Canon's Standard Test Method. Specifications are accurate at time of launch. Specifications subject to change without notice.

0042W442 Canon Hongkong Co., Ltd. 2004

PRINTED IN HONG KONG



Imagine with your IXUS.





Imagine with your I×US.