

The World's Leading DLP™ Professional Projector



EP755 / 756 / 757 Digital DLP Projectors



EP756

Specifications

Display Technology	Texas Instruments DLP™ Technology
Resolution	Native XGA (1,024 x 768), SXGA (1,280 x 1,024) compressed
Contrast (full on/off)	2000:1
Brightness	2,000 Lumens
Weight	6.6 lbs
Noise Level	32 dB in Normal Operation
Aspect Ratio	4:3 Native, 16:9 Compatible
Projection Lens	F / 2.44 ~ 2.69, f = 28.8 ~ 34.5 mm 1:1.2 Manual Zoom and Manual Focus
Video Input	D-sub 15 pin, S-video, Composite Video, DVI
Video Output	D-sub 15 pin
Throw Distance vs. Image Size (4:3)	1.14~12.4 m / 22~305 inches
Lamp type / Lamp Life	250 W User Replaceable UHP Lamp / 2,000 hour
Keystone Correction	+/-16 degree
Dimension (WxDxH)	277 x 225 x 85 mm

Conference Projector

EP755

Specifications

Display Technology	Texas Instruments DLP™ Technology
Resolution	Native XGA (1,024 x 768), SXGA (1,280 x 1,024) compressed
Contrast (full on/off)	600:1
Brightness	2,000 Lumens
Weight	6.4 lbs
Noise Level	32 dB in Normal Operation
Aspect Ratio	4:3 Native, 16:9 Compatible
Projection Lens	F / 2.44 ~ 2.69, f = 28.8 ~ 34.5 mm 1:1.2 Manual Zoom and Manual Focus
Video Input	D-sub 15 pin, S-video, Composite Video, DVI
Video Output	D-sub 15 pin
Throw Distance vs. Image Size (4:3)	1.14~12.4 m / 22~305 inches
Lamp type / Lamp Life	200 W User Replaceable UHP Lamp / 2,000 hour
Keystone Correction	+/-16 degree
Dimension (WxDxH)	277 x 225 x 85 mm

EP757

Specifications

Display Technology	Texas Instruments DLP™ Technology
Resolution	Native XGA (1,024x768), SXGA (1,280x1,024) compressed
Contrast (full on/off)	2000:1
Brightness	2,300 Lumens
Weight	6.6 lbs
Noise Level	32 dB in Normal Operation
Aspect Ratio	4:3 Native, 16:9 Compatible
Projection Lens	F / 2.44 ~ 2.69, f = 28.8 ~ 34.5 mm 1:1.2 Manual Zoom and Manual Focus
Video Input	D-sub 15 pin, S-video, Composite Video, DVI
Video Output	D-sub 15 pin
Throw Distance vs. Image Size (4:3)	1.14~12.4 m / 22~305 inches
Lamp type / Lamp Life	250 W User Replaceable UHP Lamp / 2,000 hour
Keystone Correction	+/-16 degree
Dimensions (WxDxH)	277 x 225 x 85 mm



Available from :

Optoma Corporation

5F, NO. 108, Minchiuan Rd.,
Shindian City, Taipei, Taiwan 231, R.O.C
t +886 2 2218 2360 f +886 2 2218 2313
E-mail : sales@optoma.com.tw

<http://asia.optoma.com>