
6.0 MegaPixels

3x Optical Zoom

2.5 inch LCD

Slim & Sleek
6M



NEW





6.0 MegaPixels, 3x optical zoom

Inside its sleek metallic body, the FinePix F470 packs 6.0 megapixels of imaging performance. The high-resolution CCD sensor produces brilliantly sharp, detailed images. A high-quality 3x Fujinon optical zoom lens (35-105mm equivalent) gives you a generous range of focal lengths. Used in conjunction with the digital zoom (approximately 4.4x; max combined zoom scale of 13.2x) this versatile pocket camera handles everything from wide-angle to telephoto.

2.5 inch LCD monitor in sleek pocket-size body

Slender and compact, the FinePix F470 incorporates a big, easy-to-view 2.5 inch LCD monitor. The bright crisp display makes it easy to check settings, compose your photo, and view the beautiful results. A refresh rate of 60fps ensures a smooth, responsive LCD display image during framing and shooting.



10 scene positions

The FinePix F470 offers a full complement of convenient features. The expanded selection of 10 preset scene positions makes taking great photos effortless. In addition to the familiar "Portrait", "Landscape", "Night scene" and "Sport" positions, new settings, including "Beach & Snow", "Sunset", "Party" and "Text", ensure optimum results, whatever the situation.

Portrait
 Landscape
 Sport
 Night
 Beach & Snow

Sunset
 Museum
 Party
 Flower Close-Up
 Text



* Flower Close-Up



* Sport



* Sunset

Additional features

- 16MB internal memory
- 30fps VGA-movie recording with monaural sound
- FinePix Photo button for one-touch access to frequently used settings (image size, ISO setting and FinePix color mode)
- Continuous shooting mode
- USB interface
- Video output (NTSC/PAL)
- FinePixViewer software included for easy connection to your PC
- PictBridge compatible
- Lithium-ion rechargeable battery and battery charger included



SPECIFICATIONS

DIGITAL CAMERA FinePix F470

Number of effective pixels*	6.0 million pixels
CCD sensor	1/2.5-inch square pixel CCD
Number of recorded pixels	Still image: 2816×2112/2816×1880/2048×1536/1600×1200/640×480 pixels Movie: 640×480/320×240 pixels, 30 frames/sec., with monaural sound
Storage media	Internal memory (approx. 16MB), xD-Picture Card™ (16MB - 1GB)
File format	Still image: JPEG (Exif Ver. 2.2**)/Movie: AVI (Motion JPEG) [Design rule for Camera File system compliant/DPOF-compatible]



Number of images/recording time		Still image					Movie	
Modes		6M Fine	6M Normal	3:2 Format	3M	2M	0.3M	
Quality		2816×2112	2816×2112	2816×1880	2048×1536	1600×1200	640×480	
Number of recorded pixels		2816×2112	2816×2112	2816×1880	2048×1536	1600×1200	640×480	320×240 (30 fps)
Internal memory (16 MB)		5	10	12	20	25	124	Approx. 17 sec.
16MB		5	10	12	20	25	124	Approx. 17 sec.
32MB		10	21	24	40	51	249	Approx. 34 sec.
64MB		21	43	48	81	102	499	Approx. 70 sec.
128MB		43	86	97	163	204	999	Approx. 140 sec.
256MB		87	173	195	326	410	1999	Approx. 4.7 min.
512MB		174	347	389	652	819	3995	Approx. 9.3 min.
1GB		349	695	780	1305	1640	7996	Approx. 18.7 min.

The number of images and recording time will vary slightly depending on the type of subject.

Lens	Fujinon 3.0× optical zoom lens, F2.8 - F4.9
Lens focal length	f = 5.8mm - 17.4mm (Equivalent to 35 - 105 mm on a 35 mm camera)
Focus	Auto Focus
Focus distance	Normal: Approx. 70 cm / 2.3 ft. to infinity Macro: Wide-angle: Approx. 10 cm/3.9 in. to 80 cm/2.6 ft. Telephoto: Approx. 40 cm/1.3 in. to 80 cm/2.6 ft.
Shutter speed	2 sec. to 1/1500 sec. (depend on shooting mode)
Aperture (Wide-angle)	F2.8 to F7.0
Sensitivity	AUTO / Equivalent to ISO 64/100/200/400
Exposure control	256-zone TTL metering
Exposure mode	Programmed AE
White balance	Automatic scene recognition/Preset (Fine, Shade, Fluorescent (Daylight), Fluorescent (Warm White), Fluorescent (Cool White), Incandescent)
LCD monitor	2.5 inch, Aspect ratio: 4:3; 115,000 pixels Amorphous silicon TFT, Approx. 97% coverage
Flash	Auto flash Effective range: Wide-angle: approx. 0.7m - 4.6 m (2.3 ft. - 15.1 ft.) Telephoto: approx. 0.7m - 2.6 m (2.3 ft. - 8.5 ft.) Macro: approx. 0.3m - 0.8m (1.0 ft. - 2.6 ft.) Flash mode: Auto, Red-Eye Reduction, Forced Flash, Suppressed Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Self-timer	Approx. 10 sec./2 sec. delay
Video output	NTSC/PAL selectable
Digital interface	USB
Power source	NP-40N Rechargeable Battery (included), NP-40 or AC Power Adapter AC-5VX (optional)
Dimensions	91.9 (W) × 58.1 (H) × 19.7 (D) mm / 3.6 (W) × 2.3 (H) × 0.8 (D) in
Weight	Approx. 122 g/4.3 oz. (excluding batteries and media)

Camera functions	
<i>Digital zoom</i>	Approx. 4.4× (3× optical zoom lens is used together; Max. zoom scale: 13.2×)
<i>Shooting modes</i>	Normal: Auto, Scene Position (Portrait, Landscape, Sport, Night, Beach & Snow, Sunset, Museum, Party, Flower Close-Up, Text) Continuous: Number of recorded frames: 6MF 5 frames/6MN 10 frames/3:2 12 frames/3M 20 frames/2M 25 frames/0.3M 124 frames 640×480/320×240 pixels, 30 frames/sec., with monaural sound
<i>Movie recording</i>	Trimming, Image rotate, Automatic playback, Multi-frame playback, Sorting by date, Voice memo
<i>Copying image data</i>	Copy image data between xD-Picture Card™ and internal memory; single-frame or all-frame selectable

Accessories included	NP-40N Rechargeable Battery, Battery charger BC-40, Hand strap, USB cable, A/V cable, CD-ROM: FinePixViewer
-----------------------------	---

Optional accessories	xD-Picture Card™: 16MB, 32MB, 64MB, 128MB, 256MB, 512MB, 1GB PC Card Adapter DPC-AD CompactFlash™ Card Adapter DPC-CF Image Memory Card Reader DPC-R1 AC Power Adapter AC-5VX Rechargeable Battery NP-40 Battery charger BC-65 Soft Case SC-FX455
-----------------------------	--

Accessory availability may vary by country. Please check with your local Fujifilm representative to confirm product availability.

* Number of effective pixels:
The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

** Exif 2.2 is a newly revised digital camera file format that contains a variety of shooting information for optimal printing.

Note: The FinePix F470 is compatible with the world standard PictBridge.

Specifications are subject to change without notice.

xD-Picture Card™ and all other trademarks are the property of their respective holders.



For more information on the full range of Fujifilm digital products, please visit our Website:
<http://home.fujifilm.com/products/digital/index.html>

Fujifilm – Official Imaging Sponsor of 2006 FIFA World Cup Germany™



FUJI PHOTO FILM CO., LTD.

26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN