

6.0 MegaPixels

5x Optical Zoom

3 inch LCD

NEW



See it bigger and more brilliantly
with a 3" LCD

Bring it closer
with a powerful 5x zoom





Discover the power of a 5x optical zoom and 6.0-MegaPixel resolution

If you're looking to discover a new world of visual wonder, look no further than the FinePix F650. Packing a high-resolution 6.0-megapixel CCD sensor and advanced imaging processor, it turns out super-sharp, wonderfully detailed images. And its powerful 5x Fujinon optical zoom lens (36-180mm equivalent) give you total versatility, from landscapes and architecture to family snaps and intimate close-ups. Combined with the approximately 4.4x digital zoom, that offers a 22x total zoom range, bringing you closer to your subjects than ever before.



Wide angle



2.5X optical zoom



5X optical zoom


Stylish design with a difference: A class-leading 3.0-inch LCD monitor

While compact and stylish, the FinePix F650's metal body boasts a best-in-its-class extra-large 3.0-inch, 230,000-pixel LCD monitor. The big, brilliant view makes it a pleasure both to compose your shots and then to enjoy them afterwards. And the fast 60 fps refresh rate ensures a smooth, responsive image during framing and shooting.



Comprehensive exposure modes, including 12 scene positions

So that you'll always be ready for your best shot, the FinePix F650 provides a full range of exposure modes: Auto, Aperture-priority AE, Shutter-priority AE, Manual, and Movie modes, plus a generous selection of 12 preset scene positions including Portrait, Landscape, Night Scene, Sport, Beach, Snow, Sunset, Fireworks, Museum, Party, Flower Close-Up and Text. Whatever the situation, the FinePix F650 makes it a snap to get great results.



* Flower Close-Up

- Portrait
- ▲ Landscape
- ⚡ Sport
- 🌃 Night
- 🎆 Fireworks
- 🏛️ Museum
- 🏖️ Beach
- ❄️ Snow
- 🎉 Party
- 🌸 Flower Close-Up
- 📄 Text

Additional features

- Internal memory (approx. 26MB)
- Super Macro mode (as close as 3cm/1.2 in)
- 30 fps VGA-resolution movie recording with monaural sound
- FinePix Photo button for one-touch access to frequently used settings (image size, ISO sensitivity, and FinePix color mode)
- Continuous shooting mode
- USB interface
- Video output (NTSC/PAL)
- FinePixViewer software included for easy connection to your PC
- PictBridge compatible
- Lithium-ion rechargeable battery and battery charger included



SPECIFICATIONS

DIGITAL CAMERA FinePix F650

Number of effective pixels*	6.0 million pixels
CCD sensor	1/2.5-inch square pixel CCD
Number of recorded pixels	Still image: 2816×2112/2816×1880/2048×1536/1600×1200/640×480 pixels Movie: 640×480/320×240 pixels, 30 frames/sec., with monaural sound
Storage media	Internal memory (approx. 26MB), xD-Picture Card™ (16MB - 1GB)
File format	Still image: JPEG (Exif Ver. 2.2**) / Movie: AVI (Motion JPEG) [Design rule for Camera File system compliant/DPOF-compatible]

Modes	Still image						Movie	
	6M Fine	6M Normal	3:2 Format	3M	2M	0.3M	640	320
Number of recorded pixels	2816×2112	2816×2112	2816×1880	2048×1536	1600×1200	640×480	640×480 (30 fps)	320×240 (30 fps)
Internal memory (approx. 26MB)	9	19	21	35	45	219	Approx. 30 sec.	Approx. 48 sec.
16MB	5	10	12	20	25	124	Approx. 17 sec.	Approx. 27 sec.
32MB	10	21	24	40	51	249	Approx. 34 sec.	Approx. 55 sec.
64MB	21	43	48	81	102	499	Approx. 70 sec.	Approx. 110 sec.
128MB	43	86	97	163	204	999	Approx. 140 sec.	Approx. 221 sec.
256MB	87	173	195	326	410	1999	Approx. 4.7 min.	Approx. 7.4 min.
512MB	174	347	389	652	819	3995	Approx. 9.3 min.	Approx. 14.8 min.
1GB	349	695	780	1305	1640	7996	Approx. 18.7 min.	Approx. 29.6 min.

The number of images and recording time will vary slightly depending on the type of subject.

Lens	Fujinon 5.0x optical zoom lens, F2.8 - F4.7
Lens focal length	f=5.8mm - 29mm (Equivalent to 36 - 180mm on a 35mm camera)
Focus	Auto Focus
Focus distance	Normal: Min. 60cm/2.0 ft. to infinity Macro: Wide-angle: Min. 12cm (4.7 in.) to 80cm (2.6 ft.) Super Macro: Wide-angle: Min. 3cm (1.2 in.) to 20cm (7.9 in.)
Shutter speed	2 sec. to 1/2000 sec. (depend on shooting mode)
Aperture (Wide-angle)	F2.8 to F8.0
Sensitivity	AUTO / Equivalent to ISO 64/100/200/400
Exposure control	256-zone TTL metering
Exposure mode	Programmed AE / Aperture priority AE / Shutter priority AE
White balance	Automatic scene recognition/Preset (Fine, Shade, Fluorescent (Daylight), Fluorescent (Warm White), Fluorescent (Cool White), Incandescent)
LCD monitor	3.0 inch, Aspect ratio: 4:3; 230,000 pixels low-temperature polysilicon TFT, Approx. 100% coverage
Flash	Auto flash Effective range: Wide-angle: approx. 0.6m - 4.6m (2.0 ft. - 15.1 ft.) Telephoto: approx. 0.6m - 2.7m (2.0 ft. - 8.9 ft.) Flash mode: Auto, Red-Eye Reduction, Forced Flash, Suppressed Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Self-timer	Approx. 10 sec./2 sec. delay
Video output	NTSC/PAL selectable
Digital interface	USB
Power source	NP-40N Rechargeable Battery (included), NP-40 or AC Power Adapter AC-5VX (optional)
Dimensions	104.7 (W) × 60.6 (H) × 30.8 (D) mm / 4.1 (W) × 2.4 (H) × 1.2 (D) in.
Weight	Approx. 170 g/6.0 oz. (excluding batterie and media)

Camera functions	
Digital zoom	Approx. 4.4x (5x optical zoom lens is used together; Max. zoom scale: 22.0x)
Shooting modes	Normal: Auto, Scene Position (Portrait, Landscape, Sport, Night, Fireworks, Sunset, Beach, Snow, Museum, Party, Flower Close-Up, Text), Aperture-priority AE, Shutter-priority AE Continuous: Number of recorded frames: 6MF 6 frames/6MN 12 frames/3:2 13 frames/3M 22 frames/2M 29 frames/0.3M 140 frames
Movie recording	640×480/320×240 pixels, 30 frames/sec., with monaural sound
Playback	Trimming, Image rotate, Automatic playback, 30 Multi-frame playback, Sorting by date, Voice memo
Copying image data	Copy image data between xD-Picture Card™ and internal memory; single-frame or all-frame selectable

Accessories included	NP-40N Rechargeable Battery, Battery charger BC-40, Hand strap, USB cable, A/V cable, CD-ROM: FinePixViewer
----------------------	---

Optional accessories	xD-Picture Card™: 64MB, 128MB, 256MB, 512MB, 1GB PC Card Adapter DPC-AD CompactFlash™ Card Adapter DPC-CF Image Memory Card Reader DPC-RI AC Power Adapter AC-5VX Rechargeable Battery NP-40 Battery charger BC-65S Soft Case SC-FXA03
----------------------	---

Accessory availability may vary by country. Please check with your local Fujifilm representative to confirm product availability.

* Number of effective pixels:
The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

** Exif 2.2 is a newly revised digital camera file format that contains a variety of shooting information for optimal printing.

Note: The FinePix F650 is compatible with the world standard PictBridge.

Specifications are subject to change without notice.

xD-Picture Card™ and all other trademarks are the property of their respective holders.



For more information on the full range of Fujifilm digital products, please visit our Website: <http://www.fujifilm.com/products/digital/index.html>

Fujifilm - Official Imaging Sponsor of 2006 FIFA World Cup Germany™



FUJI PHOTO FILM CO., LTD.

26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN