



Too good to share.



MP510 best buy! BenQ Digital Projector

Hit it big

Want to watch a movie or deliver a presentation in grand style? Without spending a bundle? If so, then the BenQ MP510 digital projector is just the ticket. For fun or for work, it's got the elegant design, and handy features that'll make it a hit with you.

Designed to delight

The stylishly designed MP510 will look great in your living room--or in a client's meeting room. And at an incredibly low 22dB, the MP510 is the quietest projector in the market.

Pleasing picture quality

Built for solid performance with a 1500-lumen lamp and 2000:1 contrast ratio, the MP510 adds wall color correction so you and your audience can enjoy picture quality that's easy on the eyes even when a projector screen is not available.

Enhance your enjoyment

The MP510 gives you advanced features like auto-off, seven picture modes, and even a presentation timer. What's more, the controls are easy to bring up and dismiss, so you can stay focused on enjoying a movie or giving your presentation.

BenQ
Enjoyment Matters

MP510

BenQ Digital Projector



Specifications

Native Resolution	SVGA (800 x 600)	
Projection System	DLP®	
Brightness	1500 ANSI lumens	
Lamp	160W, 2000/3000 hours (Normal/Economic mode)	
Contrast Ratio (FOFO)	2000:1	
Weight	5.7 lbs (2.6kg)	
Noise Level	26/22 dB (Normal/Economic mode)	
Resolution Support	640 x 350 to 1280 x 1024	
Dimension (WxHxD)	10.9 x 3.74 x 8.19 inches (277 x 95 x208 mm)	
Image Size	30" to 200"	
Throw Ratio	50"@2m	
Throw Distance	Min: 1.00m; Max: 8.00m	
Lens	F=2.57 (Fixed)	
Color	Full 16.7 million color palette	
Aspect Ratio	4:3/16:9 screen selectable	
Horizontal Frequency	31-82 KHz	
Vertical Scan Rate	48-85 Hz	
Projection Position	Front/Rear, Table/Ceiling	
Input Terminals	Analog RGB: D-sub 15 pin x 1 Component Video: D-sub 15 pin (Shared with Analog RGB connector) S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 USB x 1	
Control Terminals	RS232 serial control: Mini Din 8 pin x 1	
Video Compatibility	NTSC/PAL/SECAM	
Auto Switching Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power Consumption	Max 250W	
On-Screen Display Language	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/Korean/Swedish/ Dutch/ Turkish/ Czech/ Portuguese/ Thai/ Polish (17 languages)	
Picture Modes	PC Input : Dynamic mode Presentation mode sRGB mode Cinema mode	A/V Input : Dynamic mode Standard mode Cinema mode
Functions	<ul style="list-style-type: none"> • Wall color correction • Resolution reminder • Blank (Eco Mode) • High altitude mode • 7 sets of picture mode • HDTV compatible • Macintosh® compatible 	<ul style="list-style-type: none"> • Presentation Timer • Auto adjustment • Auto off • Security password • Auto source detection • "Mode" hot key
Special Features	<ul style="list-style-type: none"> • 22dB noise level • Wall Color Correction • Presentation Timer 	
Accessories (Standard)	<ul style="list-style-type: none"> • User's manual • Manual CD • PWR cord 	<ul style="list-style-type: none"> • Quick start guide • VGA cable • Remote Control
Accessories (Optional)	<ul style="list-style-type: none"> • Universal ceiling mount • Spare lamp kit 	<ul style="list-style-type: none"> • Presentation Plus • Soft carry case




Accessories (Optional)



Presentation plus
(5J.J9301.001)



Universal ceiling mount
(5J.J2K01.001)



Spare lamp kit
(5J.J2C01.001)



Soft carry case
(4G.01203.001)

Headquarters

BenQ Corporation
Digital Media Business Group
157 Shan-Ying Rd., Gueshan
Taoyuan 333, Taiwan, R.O.C.
Tel: +886-3-359-5000
Fax: +886-3-359-9000

America
BenQ America Corp.
53 Discovery Irvine,
CA 92618, U.S.A
Tel +1-949-255-9500
Fax +1-949-255-9600

Europe
BenQ Europe B.V.
Ekkersrijt 4130, 5692 DC Son,
The Netherlands
Tel: +31-499-750-500
Fax: +31-499-750-599

Asia Pacific
BenQ Asia Pacific Corp.
16 Jihu Road, Neihu,
Taipei 114, Taiwan, R.O.C.
Tel: +886-2-2799-8600
Fax: +886-2-2659-1959

China
BenQ (IT) Co., Ltd.
268 Shi-Shan Road,
Suzhou 215011, China
Tel: +86-512-6825-1233
Fax: +86-512-6825-1233-2299